

Description:



Scrubber trommel machine

Scrubber-Trommel is rotary scrubber and trommel screen Integration of one set.

It consist of three major parts, hopper, rotary scrubber, trommel screen, from hopper to rotary scrubber to wash ore, Then to trommel screen for screening different material size. rotary scrubber and trommel screen Integration of one set, Greatly save the cost and the space.

Scrubber trommel have two kinds driving type, one is use gear for driving, without lining.

one is use tires for driving, with rubber lining.

The scrubber and trommel length need according to your capacity and clay percentage to process.

Feature:

1:Save the space and the cost.

2:Good washing and screening effect for sticky clay material.

3:Sieving out different size material.

4:Low operating cost, easy maintenance, low noise.

5:The length &diameter of drum, screen mesh, layer quantity of screen and Screen material can be customized.

6: Mobile type or stationary type

Scrubber-trommel Technical Specifications

Model	Capacity (t/h)	Drum diameter (mm)	Drum total length(according to your material decide scrubber and trommel length (mm)	Screen size (mm)
1245	20-30	1200	4500	5-25
1560	50-60	1500	6000	
1860	80-100	1800	6000	
2060	100-150	2000	6000	
2260	180-200	2200	6500	

Note:please provide sticky clay content,and required screen size,Then can advice you most suitable model.

Application:



Gold wash plant to Russia



Gold trommel wash plant in Africa



Trommel scrubber



WELL-TECH EQUIPMENT
威尔国际矿业装备

Heavy duty trommel scrubber